

Nothing is ever out of reach...



Davidson



A #624 Folding Fiberglass Three-Step Step Stool

For electricians, light institutional and frequent household use. Nonconductive green fiberglass rails with yellow aluminum top cap. 3" serrated steps, slip-resistant foot caps. Pinch-resistant side locks. ANSI Type II, Commercial, 225-lb. duty rating. UL Compliant. 17w x 22 spread x 24h. Shpg. wt. 7 lbs.
DAV 624-02BX **Each 110.50**

B #566 Aluminum Euro Platform Ladder

For household use. Locking 36" high platform provides large standing area. Top rail for safety and convenience. Deeply serrated extruded aluminum steps for security. Slip-resistant foot caps. ANSI Type III, Household, 200-lb. duty rating. 18" w x 31 spread x 60h. Shpg. wt. 9 lbs.
DAV 566-03BX **Each 115.34**

C #560 Steel Qwik Step™ Platform Ladder

Qwik Step™ feature for opening ease. Lightweight yet sturdy. Folds flat to only 2" deep. Loop top handrail, steel legs and serrated steps. Top step is 24" high. ANSI Type III, Household, 200-lb. duty rating. 16" w x 19½ spread x 41h. Shpg. wt. 9 lbs.

No.	Color	Each
DAV 560ALBX	Almond	48.92
DAV 560WHBX	White	48.92

D #592 Six-Foot Fiberglass Commercial Stepladder

Channeled nonconductive fiberglass rails for strength and corrosion resistance. Deeply serrated U-channel 3" steps. Angle bracing strengthens and stabilizes top step, bottom step and rear brace. Yellow molded plastic top holds quart paint can and has slots for small hand tools. Pinch-resistant, heavy-gauge outside side locks. ANSI Type II, Commercial, 225-lb. duty rating. 22" w x 43½ spread x 72h. Shpg. wt. 16 lbs.
◆DAV 592-06BX **Each 183.08**

- All ladders meet or exceed ANSI and OSHA safety codes
- Select ladder of proper duty rating to support combined weight of user and materials
- **WARNING:** Metal ladders conduct electricity. Do not use where contact may be made with live electrical circuits