Version 2.3

Revision Date 12/22/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	Boardwalk Dust Mop Treatment	BWK352A
Material number	:	1041289 / A06412	
Manufacturer or supplier's	deta	ails	
Company	:	Boardwalk / Essendant Co.	
Address	:	One Parkway North Deerfield, IL 60015	
Telephone	:	844-828-5617	

Emergency telephone numbers				
:	844-828-5617			
:				
:	Chemtel: 1(800)255-3924			
	:			

Recommended use of the chemical and restrictions on use

Recommended use : Floor Care

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	characteristic

GHS Classification

Gases under pressure Skin irritation	: Liquefied gas : Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation.
Precautionary statements	 Prevention: P264 Wash skin thoroughly after handling. P280 Wear protective gloves. Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P332 + P313 If skin irritation occurs: Get medical advice/ attention.

Version 2.3

Revision Date 12/22/2016

BWK352A Print Date 03/21/2017

P362 Take off contaminated clothing and wash before reuse. **Storage:** P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Concentration [%]
64742-52-5	>= 10 - < 20
64742-47-8	>= 5 - < 10
64742-96-7	>= 5 - < 10
106-97-8	>= 5 - < 10
64742-49-0	>= 5 - < 10
74-98-6	>= 1 - < 5
	64742-52-5 64742-47-8 64742-96-7 106-97-8 64742-49-0

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	: Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Move out of dangerous area.	
If inhaled	 If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician. 	
In case of skin contact	 If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes. 	
In case of eye contact	 Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. Rinse immediately with plenty of water for at least 15 minut 	tes.
If swallowed	 Clean mouth with water and drink afterwards plenty of wate Keep respiratory tract clear. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 	¥r.
Most important symptoms and effects, both acute and delayed	 Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Causes skin irritation. Review section 2 of SDS to see all potential hazards. 	

Version 2.3

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	 Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid contact with skin and eyes. For personal protection see section 8.
	Smoking, eating and drinking should be prohibited in the application area.

SAFETY DATA SHEET BOARDWALK DUST MOP Version 2.3	P TREATMENT 20N18 Revision Date 12/22/2016	BWK352A Print Date 03/21/2017
	Take precautionary measures agai Provide sufficient air exchange and Open drum carefully as content ma Always replace cap after use. Dispose of rinse water in accordan- regulations. Do not breathe vapours or spray m	l/or exhaust in work rooms. by be under pressure. ce with local and national
Conditions for safe storage :	BEWARE: Aerosol is pressurized. I exposure and temperatures over 50 or throw into fire even after use. Do red-hot objects. No smoking. Containers which are opened must kept upright to prevent leakage. Observe label precautions. Electrical installations / working ma the technological safety standards. Keep in a dry, cool and well-ventila	0 °C. Do not open by force o not spray on flames or be carefully resealed and terials must comply with
Materials to avoid :	Oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm	OSHA P0

Components with workplace control parameters

SAFETY DATA SHEET **BOARDWALK DUST MOP TREATMENT 20N18** Version 2.3

Revision Date 12/22/2016

BWK352A

Print Date 03/21/2017

		PEL	1,800 mg/m3 1,000 ppm	CAL PEL
			1,800 mg/m3	
Engineering measures	: none			
Personal protective equipr	nent			
Respiratory protection	ventilati	on is provided of	on unless adequate loca exposure assessment n recommended expos	demonstrates
Hand protection Remarks			ific workplace should b protective gloves.	e discussed
Eye protection			ations and safety showe	ers are close to
Skin and body protection	Choose		according to the amou gerous substance at th	
Hygiene measures	When u	sing do not eat o sing do not smo ands before brea		orkday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: white
Odour	: characteristic
Odour Threshold	: No data available
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: The product is not flammable.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.93 g/cm3
Solubility(ies)	

Version 2.3

Revision Date 12/22/2016

Water solubility Solubility in other solvents	: emulsifiable : not determined
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition Symptoms of Overexposure	 None known. Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
ΝΤΡ	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:		
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	3
Components:		
Distillates (petroleum), hydro Acute oral toxicity	<pre>otreated heavy naphthenic:</pre>	
Acute inhalation toxicity	: LC50 Rat: > 5 mg/l Exposure time: 4 h	
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg	
Distillates (petroleum), hydro Acute oral toxicity	otreated light: : LD50 Rat: > 5,000 mg/kg	
Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l Exposure time: 6 h	
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg	
butane: Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h	
	LC50 Rat: 1,355 mg/l	
propane: Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h	
	LC50 Rat: 658 mg/l Exposure time: 4 h	
	LC50 Rat: 1,355 mg/l	
in corrosion/irritation		

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

Version 2.3

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Distillates (petroleum), hydrotreated heavy naphthenic: Distillates (petroleum), hydrotreated light: Solvent naphtha (petroleum), heavy aliph.: butane: Naphtha (petroleum), hydrotreated light: propane:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light: Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water	: Remarks: No data available
<u>Components:</u> butane :	
Partition coefficient: n-	: Pow: 2.89
octanol/water	. 100.2.00

SAFETY DATA SHEET	OP TREATMENT 20N18	BWK352A
Version 2.3	Revision Date 12/22/2016	Print Date 03/21/2017
Mobility in soil		
No data available		
Other adverse effects		
No data available <u>Product:</u>		
Regulation	40 CFR Protection of Environme Stratospheric Ozone - CAA Sec Substances	
Remarks	This product neither contains, no with a Class I or Class II ODS as Clean Air Act Section 602 (40 C + B).	s defined by the U.S.
Additional ecological information	: No data available	
<u>Components:</u> Distillates (petroleum), hyd	drotreated light :	
Additional ecological information	: No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal	methods
----------	---------

Waste from residues	:	Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY
Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity
Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, 2.2, - Limited quantity
Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, 2.2, - Limited quantity

Version 2.3

Revision Date 12/22/2016

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312	Hazards :	Sudden Release of Pressure Hazard	
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop 65		WARNING! This product contains a chemical known to the State of California to cause cancer.	
	ethylbenzene	100-41-4	
	benzene	71-43-2	
	naphthalene	91-20-3	
		WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
	toluene	108-88-3	
	benzene	71-43-2	

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Version 2.3

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information



HMIS III:



0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms	
Signal word Hazard statements Precautionary statements	 Warning: Contains gas under pressure; may explode if heated. Causes skin irritation.
	Prevention: Wash skin thoroughly after handling. Wear protective gloves.
	Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.
	Storage: Protect from sunlight. Store in a well-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.3
Revision Date:	12/22/2016
Print Date:	03/21/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.